



POLE BASE  
ROUND

Size	Weight / Vert Ft.
12" DIA.	120 LBS. / VFT.
18" DIA.	275 LBS. / VFT.
24" DIA.	475 LBS. / VFT.
30" DIA.	750 LBS. / VFT.
36" DIA.	1,050 LBS. / VFT.

**GENERAL NOTES:**

1. DESIGN SPECIFICATIONS CONFORM TO ASTM C858 SPECIFICATIONS FOR "UNDERGROUND PRECAST CONCRETE UTILITY STRUCTURE".
2. CONCRETE COMPRESSIVE STRENGTH 4,000 PSI MINIMUM.
3. STEEL REINFORCING DESIGN TO CONFORM TO THE REQUIREMENTS OF ASTM C857 SPECIFICATIONS FOR "STRUCTURAL DESIGN FOR UNDERGROUND PRECAST CONCRETE UTILITY STRUCTURES" AND SHALL UTILIZE GRADE 60 RE-BARS CONFORMING TO THE REQUIREMENTS OF ASTM A615 OR WWF CONFORMING TO THE REQUIREMENTS OF ASTM A185 OR BOTH IF REQUIRED.
4. GROUND WIRE, ANCHOR BOLTS, COUPLINGS, AND CONDUIT FURNISHED BY CONTRACTOR.
5. HEIGHT & WIDTH VARIES PER JOB REQUIREMENTS. SEE WEIGHT PER DIAMETER / VERTICAL FOOT IN CHART.